



High-Speed Polishing Wax

*Ecoclean
Cleaning Series*

Clean & Green, Ecoclean!
Eco-friendly Formulas Make Cleaning Easy.

Page 1 of 2

Product

High-Speed Polishing Wax

Features

Formulated with a high-efficiency brightening formula, this product works with high-speed polishing machines to quickly form a glossy, transparent coating. It offers easy daily maintenance, a long service life, and comprehensively enhances the brightness of floor surfaces.

Range of Application

Terrazzo, marble, polished tiles, PVC floors, and other surfaces.

Method of Application

1. When reapplying wax to the floor, first apply the base wax and allow it to dry completely.
2. Apply evenly to the floor 1–2 times, with a 30–60 minute interval between coats to ensure each wax layer dries thoroughly.
3. Polish the floor after approximately 2–4 hours.

Technical Data

Net Volume	Packaging	Physical State	Colour
1 Gallon	4 Bottles / Carton	Liquid	White
PH Value	Specific Gravity at 20 °C		
8.7≤pH≤9.3	1.010g/cm ³		



High-Speed Polishing Wax

Ecoclean Cleaning Series

Clean & Green, Ecoclean!
Eco-friendly Formulas Make Cleaning Easy.

Page 2 of 2

Storage and Safety

- Store sealed in original container at room temperature. Do not store or use at a temperature below 5 °C.
- Avoid contact with eyes. If it accidentally enters eyes, rinse immediately with plenty of clean water for at least 15 minutes; seek medical attention if irritation persists.
- Keep out of reach of children and pets. Do not take orally. If swallowed, do not induce vomiting; rinse mouth with water and seek immediate medical advice, bringing this data sheet if possible.
- TO BE USED EXCLUSIVELY BY PROFESSIONALS. When using the product, please refer to the Material Safety Data Sheet (MSDS) and follow the label instructions on the product packaging.

Disclaimer

This technical data sheet is an information document compiled in good faith. It is correct based on our experience, but no warranty is given. These contents may be modified without prior notice and have no legal significance. The application, use or processing of the product are beyond our control and should be tested for suitability and therefore at your own risk. In no event shall we be liable to the customer or any other person for any incidental or consequential damages, however caused.