



PS

Rough Stone Protective Shield

Revontulet
Stone Polishing & Care Series

High-quality crystal and metal nanoparticles create a durable and translucent protective layer

Page 1 of 2

Product

PS Rough Stone Protective Shield

Features

Rough Stone Protective Shield is suitable for sealing and protecting various natural or synthetic materials with high water absorption, such as matte stone, flamed stone panels, antique stone panels, etc. It is particularly recommended for sealing and protecting surfaces in plazas, corridors, and garages, as well as for the back of wet-laid stones or weathered marble surfaces.

Rough Stone Protective Shield can enhance the natural color of stone, provide powerful protection against various stubborn oil and water-based stains, and prevent microbial growth. It is low odor, safe and convenient to use.

Method of Application

1. Surface Preparation

The surface must be thoroughly cleaned, free of standing water, wax, dust, oil stains and other attachments.

2. Stone Drying

The surface must be kept dry to achieve optimal penetration and prevent color inconsistency.

3. Application Process

Spray or brush the product, applying it saturatedly until the surface remains moist for several minutes without drying. For better results, a second application can be done after one hour. Ensure ventilation during application; the surface can be used normally after at least 4 hours.



PS

Rough Stone Protective Shield

Revontulet
Stone Polishing & Care Series

High-quality crystal and metal nanoparticles
create a durable and translucent protective layer

Page 2 of 2

Technical Data

| Net Volume | Packaging | Physical State | Colour |
|------------|-----------------|----------------|--------|
| 4L | 4 Cans / Carton | Liquid | Clear |

Notes for Attention

1. It is recommended to conduct a small sample test on the stone. Only proceed with large-area application if the results are satisfactory after 12 hours.
2. After cleaning with acidic detergents, the surface must be neutralized (sodium carbonate solution can be used) and dried before application.
3. Do not apply when the stone surface temperature is below 4°C or above 35°C.
4. Tightly close the bottle cap after use. Exposure to humid air may cause crystallization or inactivation in the container. Do not pour leftover application materials back into the container.
5. Smoking is prohibited at the construction site. Keep away from sparks and open flames. Store and use in a well-ventilated area.
6. If the product comes into contact with skin or eyes, immediately rinse with water and soap. Seek medical attention promptly if discomfort occurs.
7. Keep out of reach of children.

Disclaimer

This technical data sheet is an information document compiled in good faith. It is correct based on our experience, but no warranty is given. These contents may be modified without prior notice and have no legal significance. The application, use or processing of the product are beyond our control and should be tested for suitability and therefore at your own risk. In no event shall we be liable to the customer or any other person for any incidental or consequential damages, however caused.